

# MARBLE BASED PRODUCT

CHARACTERISTICS	STANDARD	UNIT	RANGE OF VALUES		
			TRADIZIONALE	URBAN GRAIN	FLAIR
 Density	EN - 14617/1	Kg/dm <sup>3</sup>	2,45 - 2,70	2,40 - 2,65	2,40 - 2,55
 Water absorption	EN - 14617/1	%w/w	< 0,35 *	< 0,20	< 0,15
 Flexural strength (bending)	EN - 14617/2	MPa	> 10	> 15	> 20
 Compressive strength	EN - 14617/15	MPa	> 80	> 80	> 100
 Abrasion resistance	EN - 14617/4	mm3	250 - 561	300-500	275 - 520
 Linear thermal expansion coefficient	EN - 14617/11	°C <sup>-1</sup>	12- 16 x 10 <sup>-6</sup>	15 - 21 x 10 <sup>-6</sup>	17 - 27 x 10 <sup>-6</sup>
 Dynamic coefficient of friction	ANSI A.137.1:2012	--	Honed 200 >0,42 Indicative values	Honed 200 >0,42 Indicative values	Honed 200 >0,42 Indicative values
 Pendulum Test Value	BS7976-2:2002 (Slider 96)	--	Honed 200 DRY >45 WET >15 Indicative values	Honed 200 DRY >45 WET >15 Indicative values	Honed 200 DRY >45 WET >15 Indicative values
 Dimensional stability	EN - 14617/12 (60 x 60 x 1,2)	Class	A	A	A
 Freeze and thaw resistance	EN - 14617/5	--	Variable depending upon marble type	Variable depending upon marble type	Resistant
 Reaction to fire	EN - 13501/1	--	A2 fl - S1	A2 fl - S1	A2 fl - S1

\* Except: Napoleon Brown, Verde Tirreno, Perlato Appia

The above data is indicative and non binding. Actual test data can be supplied on request.

